

Name: \_\_\_\_\_

## Lift Safety Quiz

1. A safety stand is also called a \_\_\_\_\_
  - a. Jack
  - b. Jack stand
  - c. Bottle jack
  - d. Safety stool
2. Why must safety stands be used after lifting a vehicle with a floor jack?
3. Tall safety stands would be used to \_\_\_\_\_
  - a. Help support the vehicle when a major component is removed from a vehicle
  - b. Lift a vehicle
  - c. Lift a component such as an engine high off the ground
  - d. Both b and c
4. Technician A says that a hoist can be stopped at any level as long as the safety latch engages. Technician B says that the vehicle should be hoisted to the top of the hoist travel for safety. Which technician is correct?
  - a. Technician A
  - b. Technician B
  - c. Both technicians A and B
  - d. Neither technicians A nor B
5. Before lowering the vehicle what should the technician do?
  - a. Be sure nothing is underneath the vehicle
  - b. Raise the vehicle enough to release the safety latch
  - c. Be sure no one will be walking under or near the vehicle
  - d. All of the above
6. When checking for stability, how high should the vehicle be raised?
  - a. About 2 inches
  - b. About 6 inch
  - c. About 1 foot
  - d. About 3 feet
7. Pad extensions may be needed when lifting what type of vehicle?
  - a. Small cars
  - b. Pickup trucks
  - c. Vans
  - d. Both b and c
8. Commonly damaged areas of a vehicle during lifting include \_\_\_\_\_
  - a. Rocker panels
  - b. Exhaust systems
  - c. Tires or body panels
  - d. All of the above
9. What precautions should be adhered to when lifting a vehicle?
10. Technician A says he parks the vehicle as close to the passenger side lift post as possible when parking the vehicle to be lifted. Technician B says he parks as close to the drivers side post as possible when parking the vehicle to be lifted. Who is correct?
  - a. Technician A only
  - b. Technician B only
  - c. Both technicians A and B
  - d. Neither technician A nor B